



PANEL CUT-OUT



PCB LAYOUT  
THICKNESS: 1.6mm

**SPECIFICATION**

**A: MATERIAL:**

1. HOUSING: PA66(BLACK), UL 94V-0
2. PIN: COPPER ALLOY, NICKEL PLATED
3. TERMINAL: COPPER ALLOY, TIN PLATED

**B: CHARACTERISTICS:**

1. RATING: 10A 250V~ TUV,KC,CCC&CQC-PSE  
15A 250V~ UL
2. INSULATION RESISTANCE: 100MΩ MIN, AT 500V DC
3. ELECTRIC STRENGTH: AC 2000V FOR ONE MINUTE

**C: APPROVALS:**

UL, CUL, TUV, KC & CCC&CQC-PSE



广东博滔电子有限公司  
GUANGDONG BOYTALL ELECTRONICS CO.,LTD

PART NO.:		NAME:	
BT-14-1A-P1P7(2.0)		AC INLET 3P SOCKET	
MODEL NO.:		SPEC.:	
BT-14-1A		IEC 60320-1, C14	
DESIGNER	CHECKED	APPROVED	NOTE:
			FILE NO.:
			S14-0003

A4				COMMON TOLERANCE DIMENSION:                   ANGULAR: .000 : ±0.1                   ±3° .00   : ±0.2 .0     : ±0.3
A3				
A2				
A1				
A0	2021.04.05	NEW REVISION	----	
REV.	DATE	DESCRIPTION	ECN NO.	A 4



UNIT: mm   SCALE: 1:1   SHEET: 1 of 1